S3219E

ELECTRIC SLAB SCISSOR LIFTS



- Self-propelled electric micro scissor lift
- Compact & nimble
- Drives through a standard doorway
- Suitable for indoor and outdoor use
- Easy to use & maintain



ELECTRIC SLAB SCISSOR LIFTS

DIMENSIONS	\$3219E
Max. working height	25 ft
Max. platform height (A)	19 ft
Platform size (stowed)	64.38 in x 27.13 in
Platform size (extended)	100.38 in x 27.13 in
Deck extension length	36 in
Overall length (C)	6 ft 2 in
Overall width (D)	32 in
Stowed height (B)	6 ft 7 in
Ground clearance (stowed)	2.5 in
Ground clearance (elevated)	0.75 in


PERFORMANCE		
Platform capacity (SWL)	550 lbs	
Max. drive height	19 ft	
Max. wind speed	28 mph	
Max. drive speed (stowed)	2.0 mph	
Max. drive speed (elevated)	0.4 mph	
Gradeability	25%	
Inside turning radius	5 in	
Outside turning radius	59 in	
Tires	non-marking solid rubber	
Controls	proportional	
Drive system	2 wheel drive	
POWER		

WEIGHT	
Weight	2,850 lbs


TURNING RADIUS

Power source

Charger



S3219E



STANDARD FEATURES

- Roll-out deck extension with dual trigger locks
- Non-marking tires
- Swing-out service trays
- Saloon door entry
- Key switch
- 2 persons + equipment capacity indoors
- 1 person + equipment capacity outdoors
- Proportional controls
- Power line to platform
- Hour meter & onboard diagnostics display
- Dual lanyard attachments points
- Operators manual
- 1 year parts & labor, 5 years structural warranty
- ANSI compliant

OPTIONS

- Special paint colors
- Flashing amber light
- 110V AC 800W inverter
- Environmental (green) oil
- CSA compliant



St.Joseph, MO 64502-1160, USA Tel: 1 (785) 989-3000

> Toll-free: 1 (800) 255-0317 Fax: 1 (785) 989-3070

Email: sales.usa@snorkellifts.com

4 x 6V 220amp hour batteries

90 - 240V, 25amp